BRITE™ 1.0


LED SUBMERSIBLE




PROJECT NAME:



BRITE 1.0 LED SUBMERSIBLE



LWC5001 HOUSING



LEDOLOGY®

SPECIFICATION SHEET

L5CW10	_	_	_	– I	_
MODEL #	WATT	LED	OPTICS	FINISH	VOLTAGE

DESCRIPTION:

Recessed axial spotlight. Aisi 316L stainless steel body, tempered glass, max. Installation depth of 3 m. Supplied with 5 m. of neoprene wiring. Elegant and discreet, it is the perfect solution when space is limited. suitable for lighting small pools, entrance areas such as stairs, hydro massage areas or interestingly, for slanting floors that create a beach effect. Watertight integrity is guaranteed by the silicon gaskets in the spotlight. Water levels must be lowered prior to the removal of the luminaire for any maintenance zpurposes.

INSTALLATION NOTE:

Must be wired in series when two or more are wired together with same driver.



SPOT LIGHT



○					
FINISH O I. STAINLESS STEEL					
WATTAGE	◯ 1W	O 2W			
VOLTAGE 12	20V 220V	<u>277V</u>			
OPTICS ○ L. 40° ○ M. 25° ○ S. 10° ○ D. DIFFUSED BEAM					

