

MODEL # FINISH LED COLOUR OPTIC WATTAGE DRIVER VOLTAGE



Faretto da incasso a soffitto/ parete, ideale per l'illuminazione di vetrine, espositori, librerie, scaffalature, gradini.



Recessed ceiling/ wall spotlight, ideal for the lighting of shop-windows, stands, bookcases, shelves, steps.

Materiale	Corpo in alluminio anticorrosivo cromato Lente in PMMA N° 4 finiture standard	
N° Led	1 x 1/2W	
Potenza assorbita	1/2W	
Collegamento	In serie rispettando la polarità	
Cablaggio	Fornito con 25 cm di cavo	
Installazione	- Cartongesso/legno: per interferenza tramite o-ring (fornito) o con molle (<i>non incluse</i>) - Muratura: con cassaforma (<i>non inclusa</i>)	
Driver switching	(<i>non inclusa</i>) 350mA (1W) p. 424 (<i>non inclusa</i>) 500mA (2W) p. 425	
Accessori	Molla cod. ML025 p. 402 Cassaforma cod. CAE25 p. 398	
Fotometrie	p. 405	

Material	Chrome-plated anticorrosive aluminium body PMMA lens No. 4 standard finishes	
Led no.	1 x 1/2W	
Power absorption	1/2W	
Connection	Series connection respecting polarities	
Wiring	Provided with a 25 cm long cable	
Installation	- On false ceiling/wood through o-ring (included) or springs (<i>not included</i>) - On brickwork with housing box (<i>not included</i>)	
Driver switching	(<i>not included</i>) 350mA (1W) p. 424 (<i>not included</i>) 500mA (2W) p. 425	
Accessories	Spring code ML025 p. 402 Housing box code CAE25 p. 398	
Photometries	p. 405	

demitri Q



IP40 CE M/M F III kg 0,020 ø mm 25



CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
L6DEM
	Q Square	I CC	1	1 6000°K 2 4000°K 3 3000°K W 2700°K 4 Red 5 Green 6 Blue	2 30° 3 60°	1 2	B White RAL9003 C Chromium-plated O Black RAL9005 R Cor-ten

demitri R

IP40 CE M/M F III kg 0,020 ø mm 25



CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
L6DEM
	R Round	I CC	1	1 6000°K 2 4000°K 3 3000°K W 2700°K 4 Red 5 Green 6 Blue	2 30° 3 60°	1 2	B White RAL9003 C Chromium-plated O Black RAL9005 R Cor-ten