$\mathbf{DITTO}^{\mathsf{TM}}$

SUSPENSION OR CEILING

TYPE:

PROJECT NAME:





Ø150 Ø380

Ø700

Design: Serge and Robert Cornelissen

A pure shape and versatility identify Ditto, hanging luminaire for diffuse lighting complete with a high efficiency LED light source and driver. It is made from epoxy powder coated finish aluminum stabilized with UV rays and provided with a satin polyethylene light diffuser. Cables for suspension in galvanized steel with a 1.2 mm diameter, 200 cm of three wire electrical cable 3x0,75 mm² and ceiling attachment in painted steel included. Dimmable version and SA emergency version (1hr of autonomy) available on request. The degree of protection against the penetration of dust, solid objects and liquids is IP40.

LEDOLOGY®

TYPE:

PROJECT NAME:

DITTO Ø150

 code
 W
 Lm (3000K)
 SL
 AL
 lifetime

 L258471*
 max 32
 E27**
 N/A

RIPPLE

*do not use halogennor incandescent lamps

**lamp not included

SL see table

AL see table

120° (LED version)

TC .30 per 3000K / .40 per 4000K

IP 40

CRI >80 (LED version)

SDCM 3 (LED version)

EEI A++ (LED version)


RG (

03 Glossy black

08 Frosted white

12 Chrome painted

36 Glossy dove grey



TYPE:

PROJECT NAME:

DITTO Ø380

code W Lm (3000K) lifetime

L258672... 25 3610 50.000h L80/B20

RIPPLE

/DIMM2 DALI /DIMM3 0-10V

SL ___LED

AL included

_____ 120°

TC .30 per 3000K / .40 per 4000K

IP 40

CRI >80

SDCM 3

EEI A++


RG (


03 Glossy black

08 Frosted white

12 Chrome painted

36 Glossy dove grey





TYPE:

PROJECT NAME:

DITTO Ø700

code W Lm (3000K) lifetime

L258674.45... 45 7280 60.000h L80/B10 L258674.65... 65 9920 50.000h L80/B10

RIPPLE

/DIMM2 DALI /DIMM3 0-10V

> SL LED

ALincluded

 \triangle 120°

.30 per 3000K / .40 per 4000K TC

IΡ 40

>80 CRI

SDCM 3

RG

EEI A++

0 03 Glossy black

08 Frosted white

12 Chrome painted

Glossy dove grey

