

MODEL # FINISH LED COLOUR OPTIC WATTAGE DRIVER VOLTAGE



Faretto da incasso a pavimento, ideale per l'illuminazione di giardini, marciapiedi e vialetti.


Recessed floor spotlight, ideal for the lighting of gardens, sidewalks and paths.

Materiale	Corpo in alluminio anticorrosivo anodizzato Flangia superiore in acciaio inox lavorato o satinato Diffusore in PMMA sabbiato N° 2 finiture standard
N° Led	3 x 1/2W
Potenza assorbita	3/6W
Collegamento	In parallelo
Cablaggio	Fornito con 50 cm di cavo bipolare in neoprene e pressacavo
Installazione	A pavimento con cassaforma <i>(non inclusa)</i>
Alimentatore	<i>(non inclusa)</i> 24V dc p. 427
Accessori	Cassaforma cod. CA060 p. 399
Note	Equipaggiato con D.O.B. System Per configurazione RGB vedi p. 431

Material	Anticorrosive anodized aluminium body Worked/satinized stainless steel top Satinized PMMA diffuser No. 2 standard finishings
Led no.	3 x 1/2W
Power absorption	3/6W
Connection	Parallel connection
Wiring	Provided with 50 cm long bipolar neoprene cable + cable gland
Installation	On the floor with housing box <i>(not included)</i>
Power supply	<i>(not included)</i> 24V dc p. 427
Accessories	Housing box code CA060 p. 399
Note	Equipped with D.O.B. System For RGB version see p. 431

fenicce

IP68NP CE F III kg 0,310 2500 73 mm WP



CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING	DIMMER
L6FEN	+
	0	V CV	3	1 6000°K 2 4000°K 3 3000°K W 2700°K 4 Red 5 Green 6 Blue	5 180°	1 2	I Worked steel S Satinized steel	D Dimmer
L6FEN	
	0	I CC	3	7 RGB	5 180°	1 2	I Worked steel S Satinized steel	