**TYPE:** 


**CEILING MOUNT** 

**PROJECT NAME:** 



## Grand ON

Grand ON is a classic item in the range surface-mounted luminaires. It features a special casing which enables directing light by turning the ring as well as a possibility of moving the light's body. The two heights facilitate the selection of luminaires to cater for the needs of a given interior, while the possibility of choosing different light sources makes it very versatile. Already when purchasing the luminaire, the client must choose either the version supporting halogen lights or LED substitutes, or the one expanded by a Lightpro module, which becomes an integral part of the light - ensuring adjustable lighting angle in the range of 15° to 50°.



APPLICATION: Basic, complementary, and spot lighting. It will work perfectly at establishments such as clubs, galleries, and hotels, but also as lighting for the office and home.



# GRAND ONTM

**CEILING MOUNT** 

#### **TYPE:**

#### **PROJECT NAME:**

		INDEX	SOURCE / OUTPUT	ENERGY GRADE	LUMINOUS FLUX	ANGLE	LIGHT COLOUR	DIMMING	POWER SUPPLY
(5.35°) Ø 136	L38 GRAND ON	07.1101.594.	hal. 111 G53 max. 50 W, all parameters according to the light source; transformer operation from 1 W					<b>120</b> V 50 Hz	
	L38 GRAND ON L11 W TRIAC	07.1103.D66.	LED 12,8 W	A++	1114 lm	15-50°	2700 K CRI≥90	TRIAC	<b>120</b> V 50 Hz
	L38 GRAND ON L11 NW TRIAC	07.1103.D67.	LED 12,8 W	A++	1114 lm	15-50°	3000 K CRI≥90	TRIAC	
	L38 GRAND ON L11 N TRIAC	07.1103.D68.	LED 12,8 W	A++	1170 lm	15-50°	4000 K CRI≥90	TRIAC	
	L38 GRAND ON L11 SNW TRIAC	07.1103.A6B.	LED 12,3 W	A++	1008 lm	15-50°	3000 K CRI≥97	TRIAC	<b>120</b> V 50Hz
	L38 GRAND ON L11 SN TRIAC	07.1103.A6C.	LED 12,3 W	A++	1146 lm	15-50°	4000 K CRI≥97	TRIAC	
(5.35°) Ø 136 (7.87°)	L38 GRAND ONI	07.1102.594.	hal. 111 G53 max	. 50 W, all par	ameters according to	the light sourc	e; transformer operatio	on from 1 W	120 V 50 Hz
	L38 GRAND ONI L21 W TRIAC	07.1104.R66.	LED 12,8 W	A++	1114 lm	15-50°	2700 K CRI≥90	TRIAC	120 V 50 Hz
	L38 GRAND ONI L21 NW TRIAC	07.1104.R67.	LED 12,8 W	A++	1114 lm	15-50°	3000 K CRI≥90	TRIAC	
	L38 GRAND ONI L21 N TRIAC	07.1104.R68.	LED 12,8 W	A++	1170 lm	15-50°	4000 K CRI≥90	TRIAC	
	L38 GRAND ONI L21 SNW TRIAC	02.1104.A6B.	LED 12,3 W	A++	1080 lm	15-50°	3000 K CRI≥97	TRIAC	<b>120</b> V 50Hz
	L38 GRAND ONI L21 SN TRIAC	02.1104.A6C.	LED 12,3 W	A++	1146 lm	15-50°	4000 K CRI≥97	TRIAC	

#### Standard



ALUMINIUM (anodised, polished)



002 BLACK (RAL 9005, fine structure)



003 WHITE (RAL 9010, fine structure)



060 SNOW WHITE (RAL 9016, fine structure)



GRAPHITE

(RAL 7015, fine structure)

### Colour options



008 ALUMINIUM/BLACK (aluminium/RAL 9005)





SHEET

ALUMINIUM/WHITE 010 (aluminium/RAL 9010)

014 BLACK/ALUMINIUM (RAL 9005/aluminium)



BLACK/WHITE (RAL 9005/RAL 9010)



BLACK/GOLDEN (RAL 9005/golden)



WHITE/BLACK (RAL 9010/RAL 9005)



SNOW WHITE/BLACK (RAL 9016/RAL 9005)



075 BLACK/SNOW WHITE (RAL 9016/RAL 9005)



072 SNOW WHITE/BLACK (RAL 9005/RAL 9016)

### How to read colour options?

