

# MONSOON™

RECESSED LED

TYPE:

PROJECT NAME:



MODEL #      FINISH      LED COLOUR      OPTIC      WATTAGE      DRIVER      VOLTAGE



Segnapasso da incasso a parete, ideale per l'illuminazione di gradini e corridoi.


Recessed wall spotlight, ideal for the lighting of steps and corridors

<b>Materiale</b>	Corpo in alluminio anticorrosione schermo di protezione in PMMA N° 2 finiture standard	
<b>N° Led</b>	2 x 1/2W	
<b>Potenza assorbita</b>	2/4W	
<b>Collegamento</b>	In serie rispettando la polarità	
<b>Cablaggio</b>	Fornito con 25 cm di cavo	
<b>Installazione</b>	- Muratura con scatola da incasso 503 ( <i>non inclusa</i> ) e viti M3 a scomparsa (fornite) - Cartongesso/Legno con molle ( <i>non incluse</i> )	
<b>Driver switching</b>	( <i>non inclusa</i> ) 350mA (1W) p. 424	( <i>non inclusa</i> ) 500mA (2W) p. 425
<b>Accessori</b>	Molla cod. ML060 p. 402	

<b>Material</b>	Anticorrosion aluminium body PMMA protection glass no. 2 standard finishings	
<b>Led no.</b>	2 x 1/2W	
<b>Power absorption</b>	2/4W	
<b>Connection</b>	Series connection respecting polarities	
<b>Wiring</b>	Provided with a 25cm long cable	
<b>Installation</b>	- On brickwork through a 503 box ( <i>not included</i> ) and screws M3 included - On false ceiling/wood with springs ( <i>not included</i> )	
<b>Driver switching</b>	( <i>not included</i> ) 350mA (1W) p. 424	( <i>not included</i> ) 500mA (2W) p. 425
<b>Accessories</b>	Spring code ML060 p. 402	

monsoon

IP40 CE M M F III kg 0,300



CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
L6MON	...	...	...	...	...	...	...
	0	I CC	2	1 ○ 6000°K 2 ○ 4000°K 3 ○ 3000°K W ○ 2700°K 4 ● Red 5 ● Green 6 ● Blue	3 ▲ 60°	1 2	A Anod. alu. B White RAL9003

SPECIFICATION SHEET