

MODEL #      FINISH      LED COLOUR      OPTIC      WATTAGE      DRIVER      VOLTAGE




Faretto da incasso a pavimento, ideale per l'illuminazione di marciapiedi, vialetti, pavimentazioni in porfido, giardini.  
Recessed floor spotlight, ideal for the lighting of sidewalks, paths, porphyty floorings, gardens.

<b>Materiale</b>	Corpo in alluminio anodizzato Vetro temperato serigrafato N° 1 finitura standard	
<b>N° Led</b>	1 x 4/6W	
<b>Potenza assorbita</b>	4/6W	
<b>Collegamento</b>	In serie rispettando la polarità	
<b>Cablaggio</b>	Fornito con 50cm di cavo in neoprene e pressacavo	
<b>Installazione</b>	A pavimento con cassaforma (non inclusa)	
<b>Driver switching</b>	(non inclusa) 350mA (4W)	p. 424
	(non inclusa) 500mA (6W)	p. 425
<b>Accessori</b>	Cassaforma cod. CA050R	p. 399
	Cassaforma cod. CA050Q	p. 399
<b>Fotometrie</b>		p. 417
<b>Note</b>	Per configurazione RGB vedi p. 431	

<b>Material</b>	Anodized aluminium body Tempered screen-printed glass No. 1 standard finishing	
<b>Led no.</b>	1 x 4/6W	
<b>Power absorption</b>	4/6W	
<b>Connection</b>	Series connection respecting polarities	
<b>Wiring</b>	Provided with 50cm long bipolar neoprene cable + cable gland	
<b>Installation</b>	On the floor with housing box (not included)	
<b>Driver switching</b>	(not included) 350mA (4W)	p. 424
	(not included) 500mA (6W)	p. 425
<b>Accessories</b>	Housing box code CA050R	p. 399
	Housing box code CA050Q	p. 399
<b>Photometries</b>		p. 417
<b>Note</b>	For RGB version see p. 431	


### shaped R



IP67 CE F III kg 0,300 500 50 WP

CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
<b>L6SHA</b>	...	...	...	...	...	...	...
	<b>R</b> Round	<b>I</b> CC	<b>1</b>	<b>2</b> 4000°K <b>3</b> 3000°K <b>W</b> 2700°K <b>7</b> RGB	<b>1</b> 16° <b>2</b> 40° <b>3</b> 64° <b>4</b> 120° <b>W</b> Wall wash 16°x40°	<b>4</b> <b>6</b>	<b>O</b> Black RAL9005

### shaped Q



IP67 CE F III kg 0,400 500 50 WP

CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
<b>L6SHA</b>	...	...	...	...	...	...	...
	<b>Q</b> Square	<b>I</b> CC	<b>1</b>	<b>2</b> 4000°K <b>3</b> 3000°K <b>W</b> 2700°K <b>7</b> RGB	<b>1</b> 16° <b>2</b> 40° <b>3</b> 64° <b>4</b> 120° <b>W</b> Wall wash 16°x40°	<b>4</b> <b>6</b>	<b>O</b> Black RAL9005