
| LIGHTING FEATURES     |  |
|-----------------------|--|
| LED COLOUR            | RGBW   |
| OPTICS                | Diffused   |
| AVERAGE LED LIFE      | 50.000h L80 B10  |
|                       |  |
| MECHANICAL FEATURES   |  |
| WEIGHT                | Kg 0,16  |
| FINISHES              | Glass  |
| INSTALLATION          | Recessed in ground with housing box , recessed in brickwork with housing box |
| MATERIAL              | Anticorodal aluminum body, tempered sandblasted glass                        |
| GENERAL FEATURES      |  |
| OPERATING TEMPERATURE | -10°C +45°C  |
| INGRESS PROTECTION    | IP67   |
| IMPACT RESISTANCE     | IK10   |
| GLOW WIRE TEST        | 960°C  |
| CLASS                 | II   |



| ORDERING INFO      |                      |       |                                |
|--------------------|----------------------|-------|--------------------------------|
| L01TIR11RGB        | -                    | - RGB | -                              |
| Model (Order Code) | Accessories          | LED   | Remote Driver                  |
| ○L01TIR11RGB 4W    | ○ CAR41: Housing Box | ○ RGB | ○ 120V LTE<br>○ 120-277V 0-10V |



## TIRESIA™ S RGB

## **TYPE:**

**RECESSED - ACCESSORIES** 

## **PROJECT NAME:**

| CODE     | CAR41            |          |
|----------|------------------|----------|
| TYPOLOGY | Housing box      | A kg 0,6 |
| MATERIAL | PVC, Dima in PLA |          |

