

ZEFIRA

RECESSED LED

TYPE:

PROJECT NAME:



MODEL # FINISH LED COLOUR OPTIC WATTAGE DRIVER VOLTAGE



Faretto da incasso a soffitto/ parete, ideale per la realizzazione di cieli stellati e per l'illuminazione di centri benessere.


Recessed ceiling/ wall spotlight, ideal for the creation of stary skies and the lighting of spa.

Materiale	Corpo in alluminio anticorodal anodizzato Diffusore in PMMA N° 1 finitura standard
N° Led	1 x 1W
Potenza assorbita	1W
Collegamento	In serie rispettando la polarità
Cablaggio	Fornito con 25 cm di cavo
Installazione	Zefiro S-M - Cartongesso/legno: per interferenza tramite o-ring (fornito) o con molle (<i>non incluse</i>) Zefiro M - Muratura: con cassaforma (<i>non inclusa</i>)
Driver switching	(<i>non inclusa</i>) 350mA (1W) p. 424
Accessori	Molla cod. ML015 (S) p. 402 Molla cod. ML025 (M) p. 402 Cassaforma cod. CAE25 (M) p. 398
Fotometrie	p. 406
Note	Per configurazione RGB vedi p. 431

Material	Anticorodal anodized aluminium body PMMA diffuser No. 1 standard finishing
Led no.	1 x 1W
Power absorption	1W
Connection	Series connection respecting polarities
Wiring	Provided with a 25 cm long cable
Installation	Zefiro S-M - On false ceiling/wood through o-ring (included) or springs (<i>not included</i>) Zefiro M - On brickwork with housing box (<i>not included</i>)
Driver switching	(<i>not included</i>) 350mA (1W) p. 424
Accessories	Spring code ML015 (S) p. 402 Spring code ML025 (M) p. 402 Housing box code CAE25 (M) p. 398
Photometries	p. 406
Note	For RGB version see p. 431

zefira S


IP40 CE M M F III kg 0,030 ø mm 16



CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
L6ZEF
	S Ø19mm	I CC	1	1 6000°K 2 4000°K 3 3000°K W 2700°K 4 Red 5 Green 6 Blue	4 120°	1	P PMMA

zefira M

IP40 CE M M F III kg 0,05 ø mm 25



CODE	OPTIONS	SUPPLY	N°LED	LED COLOUR	OPTICS	WATT	FINISHING
L6ZEF
	M Ø30mm	I CC	1	7 RGB	4 120°	1	P PMMA

SPECIFICATION SHEET