

METRO™ C

CEILING MOUNT

TYPE:

PROJECT NAME:



SPOTLIGHTS

Metro C is a medium-output spotlight with adjustable lighting direction and angle (from 15° to 50°). When the spotlight is oriented downwards, the light is equipped with a diffuser screen covering the inside of its casing. When the light changes its direction, the diffuser screen does so as well, thus dynamically changing the light's shape.

General, complementary, and spot lighting. It will work perfectly at establishments such as clubs, galleries, and hotels, but also as lighting for the office and home.



ORDERING INFO

Model	Finish	Output	LED	Voltage	Dimming
<input type="radio"/> L3854.6101 (1 light)	See below	<input type="radio"/> LED 12.8W per light	<input type="radio"/> 27K (2700K)	<input type="radio"/> 120V	<input type="radio"/> LTE (Leading/Trailing Edge Dim)
<input type="radio"/> L3854.6102 (2 lights)		<input type="radio"/> SLED 12.3W per light	<input type="radio"/> 30K (3000K) <input type="radio"/> 40K (4000K)	<input type="radio"/> 277V	<input type="radio"/> 010V (0-10V)

FINISH OPTIONS



SPECIFICATION SHEET

LEDOLOGY®

A Luminart BRAND

WWW.LEDOLOGY.COM
Last updated: 12/16/19