

# SOFTLIGHT™

CEILING


TYPE:

PROJECT NAME:




Softlight is a line of fixtures designed to limit glare to the biggest possible extent while retaining the highest parameters of light quality. All luminaires in this line feature light sources slightly moved back into the body. They look superb fitted as single units or more sophisticated light installations.

FINISHES:  
 002 Black  
 060 Snow White  
 003 White  
 006 Graphite  
 101 Gray



	INDEX	SOURCE / OUTPUT	LUMINOUS FLUX	ANGLE	LIGHT COLOUR
SOFTLIGHT C S 2700	L3854.1103.Dx6.	LED 12.6 W	1440 lm	—	2700 K CRI≥95
SOFTLIGHT C S 3000	L3854.1103.Dx7.	LED 12.6 W	1440 lm	—	3000 K CRI≥95
SOFTLIGHT C S 4000	L3854.1103.Dx8.	LED 12.6 W	1540 lm	—	4000 K CRI≥95



SOFTLIGHT C B 2700	L3854.1104.Ax6.	LED 20 W	2650 lm	—	2700 K CRI≥95
SOFTLIGHT C B 3000	L3854.1104.Ax7.	LED 20 W	2650 lm	—	3000 K CRI≥95
SOFTLIGHT C B 4000	L3854.1104.Ax8.	LED 20 W	2800 lm	—	4000 K CRI≥95

SPECIFICATION SHEET



## ORDERING INFO

Model (Order Code)	Finish	LED	Driver Options
	<input type="radio"/> 002 Black	<input type="radio"/> 2700K	<input type="radio"/> 120V Phase Dimming
	<input type="radio"/> 003 White	<input type="radio"/> 3000K	<input type="radio"/> 120V 0-10V Dimming
	<input type="radio"/> 060 Snow White	<input type="radio"/> 4000K	<input type="radio"/> 277V 0-10V Dimming
	<input type="radio"/> 006 Graphite		
	<input type="radio"/> 101 Gray		



LEDOLOGY®

A **Luminart** BRAND

WWW.LEDOLOGY.COM  
 Last updated: 6/01/21