## **SPUN**<sup>TM</sup>

## TYPE:

## **CEILING**

## **PROJECT NAME:**



Spun is a surface mounted luminaire featuring a light source slightly moved back into the luminaire body and a soft prism diffuser which reduces glare and softens the light pleasantly.

FINISHES: 002 Black 060 Snow White 003 White 006 Graphite 101 Gray

		INDEX	SOURCE / OUTPUT	LUMINOUS FLUX	ANGLE	LIGHT COLOUR
Ø 5.47" Ø 139	SPUN CEILING 2700	L3833.1110.Dx6.	LED 20 W	2650 lm	_	2700 K CRI≥95
	SPUN CEILING 3000	L3833.1110.Dx7.	LED 20 W	2650 lm	_	3000 K CRI≥95
4.33 1110 90.9	SPUN CEILING 4000	L3833.1110.Dx8.	LED 20 W	2800 lm	_	4000 K CRI≥95
Ø 6.27"						

SHEET	002	003	060	006
S	ORDEF	RING	NFO	
Z	CHEL			
O				
SPECIFICATION		Mod	lel (Order	Code)
$\circ$				
표				
_				
E (	((II)			
SP	Intertek			

006	101

ORDERING INFO	_	_	_
Model (Order Code)	Finish	LED	Driver Options
	O02 Black	○ 2700K	
	O03 White	○ 3000K	
	O60 Snow White		277V 0-10V Dimming
	O06 Graphite		
Intertek	O 101 Gray		